

**CHAIN OILS** are available in three grades - heavy, medium and light - and are blended using highly refined mineral base stocks and a specially-formulated additive package designed to reduce 'fling' and offer excellent all round performance for many general purpose industrial applications.

## APPLICATION

Designed for the lubrication of all types of drive and conveyor chains, bearings and linkages in a wide range of applications. Select the appropriate grade and apply per the equipment manufacturers instructions.

## BENEFITS

- Formulated to include anti-wear capabilities for prolonged chain life.
- Special 'tackifier' reduces 'fling' and ensures that the film of oil is not ejected from the chain.
- Excellent penetration into pins and links.
- Enhanced anti-corrosion protection capabilities.
- Offers wide operating temperature ranges between -15°C and +120°C.

## TYPICAL PROPERTIES

	HEAVY	MEDIUM	LIGHT
Viscosity @ 40°C	150	100	68
Colour	Amber	Amber	Amber
Density	0.891	0.887	0.882

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.