

Last Updated: 07.01.2016  
Code: AE0008M

**FLEETLUBE 15w40** engine oil is designed to meet the requirements of both turbocharged and naturally aspirated diesel and petrol engines. Manufactured from high quality mineral base oils incorporating high performance viscosity index improvers, anti-oxidant, anti-wear and detergent dispersant additives for extended engine life.

## APPLICATION

For use in light and heavy duty commercial vehicles, vans, off highway plant and passenger cars where this specification of oil is required by the manufacturer.

## BENEFITS

- High shear stability.
- Excellent sludge control for stop start motoring.
- Anti-wear performance for reduce engine wear.
- Bore polish protection.

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CG-4/SJ
- ACEA E3, A3/B3
- Mercedes-Benz 228.3 / 229.1
- VOLVO VDS
- MACK EO-M
- MAN 3275
- VW 501.00/505.00

## TYPICAL PROPERTIES

Specific Gravity @ 15.6°C:	0.881	Flash Point COC (°C):	220
Kinematic Viscosity @ 100°C (cSt):	14.2	Pour Point (°C):	-32
Kinematic Viscosity @ 40°C (cSt):	108.9	TBN mg KOH/g:	9.18
VI:	141		

## HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.