

Last Updated: 30.04.2020

Product Codes: AE0017, AE0422, AE0009, AE0307, AE0308

**FLEETLUBE 10, 20, 30, 40 and 50** are monograde engine oils designed to meet the requirements of many naturally aspirated diesel and petrol engines.

## APPLICATION

Primarily for use in commercial vehicles, vans, plant, off-highway equipment and passenger cars where this specification of oil is required by the manufacturer. Fleetlube SAE 30 is also commonly used in many types of smaller agricultural machinery, such as 4 stroke petrol-engined lawnmowers.

## BENEFITS

An API SG/CF specification diesel/petrol engine oil which can also be used in many transmission and hydraulic applications for plant, off-highway and agricultural equipment which require 10w, 20w, SAE 30, SAE 40 & SAE 50 viscosities.

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SG/CF
- MAN 270 (SAE 30 and SAE 40 only)
- MB 228.0 (SAE 30 and SAE 40 only)

## TYPICAL PROPERTIES

	<u>10w</u>	<u>20w</u>	<u>SAE 30</u>	<u>SAE 40</u>	<u>SAE 50</u>
Kinematic Viscosity @ 100°C (cSt):	4.9	7.4	10.2	13.8	17.6
Density @ 15.6°C:	0.869	0.880	0.888	0.893	0.889

## HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.