

HYPOID GEAR OILS SAE 90, 80w90 & 85w140 GL5 are heavy duty hypoid axle lubricants.

APPLICATION

A range of hypoid gear oils formulated for use in a wide variety of gearboxes and axles requiring high levels of extreme pressure (EP) performance to API GL5 specification in various viscosities.

BENEFITS

- Specially selected additives combined with high quality solvent refined base stocks including enhanced EP performance.
- Excellent protection from wear
- Anti-rust characteristics
- Good oxidation stability
- Imparts exceptional load carrying ability
- Meets or exceeds API GL5 / MIL-L-2105D

TYPICAL PROPERTIES

PRODUCT	SAE 90 GL5	80w90 GL5	85w140 GL5
Density @ 15.6°C	0.898	0.894	0.899
Viscosity @ 40°C	156.0 cSt	155.0 cSt	420.0 cSt
Viscosity @ 100°C	17.1 cSt	17.0 cSt	28.0 Cst
Viscosity Index	119	118	92
Flash Point (PMCC)	200°C	200°C	210°C
Pour Point	- 25°C	- 25°C	- 15°C

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.