

Last Updated: 05.08.2019

Product Code: MW0832

SARCUT 832 is an extreme pressure neat cutting oil formulated with a blend of high quality, low aromatic mineral and synthetic components and a carefully balanced additive system.

APPLICATION

Suitable for use in applications where high levels of extreme pressure additives are required, such as fine blanking, forming and piercing on high speed transfer presses, as well as heavy duty broaching operations and other metalworking operations where high levels of EP performance are required.

BENEFITS

- Low odour promotes a high level of operator acceptability.
- Multi-metal compatibility - non-staining towards yellow metals, brass, copper etc.
- Formulated to protect and extend the life of tooling and enhance component finish.
- Low viscosity ensures good flushing of machine swarf and debris.

TYPICAL PROPERTIES

Appearance:	Clear pale straw liquid
Odour:	Low
Specific Gravity@ 15.6°C:	1.015-1.020
Viscosity @ 40°C:	25-28 cSt
Flashpoint:	> 190°C
Sulphur:	No
Chlorine:	Yes
Ester:	Yes

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.