Technical Data Sheet

SAR Lubricants

Last Updated: 19.11.2009
Product Code: MW0435

SARCUT CASF 15 is an extreme pressure neat cutting oil blended from solvent refined mineral oil using selected additives, affording a high level of lubricity and EP performance.

APPLICATION

Suitable for machining a wide range of materials in various applications, including deep hole boring, broaching, H.D. tapping, threading and gear cutting. Arduous operations are overcome using high performance EP package.

BENEFITS

- Enhanced lubricity
- Good workpiece visibility
- Improved finish on machine parts
- Low oil mist levels
- Promotes extended tool life

TYPICAL PROPERTIES

Appearance:	Amber Fluid
Specific Gravity @ 15.6°C:	0.890 – 0.900
Kinematic Viscosity @ 40°C:	13.5 – 16.5 cSt
Sulphur:	Yes
Chlorine:	Yes
Ester:	Yes

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, MIRFIELD,
West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371
Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk
Registered In England: 05866783 VAT Registration No: 889171963

Certificate Number
12669
ISO 9001