

Last Updated: 23.03.2018

Product Code: MW0419

SARCUT CUTTING & TAPPING PASTE is based on a highly effective combination of extreme pressure and lubricity additives to promote ease of cutting and prolong tool life.

APPLICATION

A waxy paste usually applied by dipping the tool in the product. Effective on high alloy steels and can be used on all non-ferrous metals. Optimum consistency so that the lubricant clings to the metal surface even on the highest speed applications.

BENEFITS

- Drilling, sawing and thread cutting simplified
- Safe on steels, copper, brass, stainless steel and ceramics
- Extends tool life
- High rates of metal removal
- High anti weld features
- Silicone and CFCs Free
- Reduces heat and improves surface finish
- Non-drip compound for brush application or dipping small cutting tool

TYPICAL PROPERTIES

Appearance Brown thixotropic paste
Melting Point 45-50°C

AVAILABLE PACK SIZES

3 Kg Tins (5 x 3 Kg per case)

HEALTH & SAFETY, STORAGE AND DISPOSAL

SARCUT CUTTING & TAPPING PASTE should be stored in dry conditions and protected from extreme temperatures: between 4°C and 35°C is the recommended storage temperature.

SARCUT CUTTING & TAPPING PASTE is unlikely to present any significant health or safety hazard when used as recommended by SAR Lubricants. Good standards of personal and industrial hygiene are to be maintained by the user (see Material Safety Data Sheets). In order to protect the environment, the product used should be safely disposed by a licensed contractor. The packaging material should be handled by a recognised reconditioning firm.

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. SAR Lubricants assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of SAR Lubricants