

Last Updated: 14.09.2016  
Product Code: MW0150

**SARFORM 150** is a custom blend of mineral oils and selected high performance additives designed for heavy duty metal forming operations.

## APPLICATION

Formulated primarily for use in severe deep drawing and other heavy duty metal forming operations on steel, stainless steel and other steel alloys, as well as aluminium and aluminium alloys. Suitable for use in stainless steel and alloy steel tube cold pilgering operations, as well as many other arduous applications where extreme or heavy duty performance is desirable.

## BENEFITS

- Low odour and pale colour for enhanced operator acceptability.
- Contains high performance, chlorinated EP additives to provide high resistance to wear.
- Formulated to promote enhanced tool and dye life, and provide high resistance to extremes of temperature and pressure.
- Offers flexibility and suitability for use in a wide range of operations and materials.

## TYPICAL PROPERTIES

|                           |   |                   |
|---------------------------|---|-------------------|
| Appearance                | - | Pale amber liquid |
| Specific Gravity @ 15.6°C | - | 1.04              |
| Viscosity @ 40°C          | - | 135-165 cSt       |

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.