

Last Updated: 19.02.2014

Product Code: IP 0391

SARTEC 30 is a medium viscosity rust preventative dewatering fluid which leaves a thin protective film. Formulated with a blend of corrosion inhibitors and waxes in a hydrocarbon base. Will give 3-6 months indoor storage protection and 2-4 months covered outdoor protection.

APPLICATION

Use as received and apply by spray, brush or dipping in a well ventilated area. Leaves a waxy film on drying.

BENEFITS

- Safe on both ferrous and non-ferrous metals.
- Provides short to medium term protection of metal components when stored undercover.
- Easily removed with hydrocarbon solvents.
- Excellent penetration.
- Non-staining.
- Ideal as a protectant for agricultural machinery, steel stocks etc.

TYPICAL PROPERTIES

Appearance:	Fluid Oil	Specific Gravity @ 15.6°C:	0.8342
Colour:	Amber	Indoor Protection:	3-6 Months
Flash Point:	64°C	Kinematic Viscosity @ 40°C:	8.5 cSt

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.