

Last Updated: 07.08.2019

Product Code: AT0035

**SARTRAC STOU 15w30** is a multipurpose lubricant suitable for use in agricultural tractor engines, transmissions and hydraulic systems requiring these performance profiles.

## APPLICATION

Use as received in engines, transmissions, hydraulic systems, power take-off systems, power steering units, hydrostatic transmissions and gear drive units when one multi-functional lubricant of this specification is recommended or required. A cost-effective grade, especially suitable for older equipment where more modern specifications are not a requirement.

## BENEFITS

- One oil for several applications, so reducing the number of grades needed in stock
- Wide-ranging specification assures compliance with many manufacturer requirements
- Reduces the risk of filling the wrong lubricant when several applications are due for changing
- Excellent cold weather performance
- Suitable for wet brake applications

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CE / SF, API GL-4
- ACEA E2
- Ford M2C-159B
- Massey Ferguson M1135, M1139
- Allison C3
- John Deere J20A, J20B, J27
- CAT TO-2
- ZF TE-ML 06A

## TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C: 12.5 cSt  
Specific Gravity @ 15.6°C: 0.890

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.