

Last Updated: 14.12.2018

Product Code: AE0538

SYNMAX 5w30 is a high performance full synthetic engine oil designed for use in both petrol and diesel engines in passenger cars, vans and light commercial vehicles.

APPLICATION

Recommended for use as a crankcase lubricant for vehicles where this grade of oil is required. Formulated to meet the ACEA normal SAPS requirements, and so not suitable for use where a low SAPS engine oil is specified by the engine manufacturer.

BENEFITS

- Provides quick circulation of the oil even under cold start conditions.
- Helps maximise fuel economy.
- Formulated to help minimise emissions.
- Offers enhanced protection against wear even under arduous conditions.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API SL/CF
- ACEA A3/B4
- VW 502.00/505.00
- Mercedes Benz 229.3/229.5
- Renault RN 0700/ RN 0710

TYPICAL PROPERTIES

Kinematic Viscosity @ 100°C:	12.1 cSt
TBN mg KOH/g (ASTM D-2896):	11.02
Viscosity Index:	170
Density @ 15.6°C:	0.851

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.