

Last Updated: 08.07.2014
Product Code: GR0907/180KG

WTL 2 GREASE is a specially developed multi-purpose lithium complex grease for lubricating all anti-friction and plain bearings for use in industrial and automotive applications – provides exceptional performance characteristics over a wide operating temperature range.

APPLICATION

Can be applied manually, or via a central lubricating system designed for, and capable of, pumping an NLGI No.2 grease. NB : please consult a qualified centralised lubrication systems engineer before installation.

Take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Exceptional mechanical stability extends relubrication intervals
- Excellent corrosion protection protects components operating in wet conditions
- Superior anti-oxidation capability provides lasting protection even at high temperatures
- Excellent EP and anti-wear performance

TYPICAL PROPERTIES

Appearance:	Brown smooth grease
NLGI classification:	2
Base Oil:	Solvent refined mineral oil
Thickener:	Lithium complex
Copper corrosion (IP112):	Pass
Resistance to corrosion EMCOR (IP220)	0 : 0
Operating temperature range:	-20°C to + 150°C
Water washout (IP215): @38°C	3%
Dropping point (IP132):	250°C max

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.