

AGRISTAR SHPD 15W40 is a heavy-duty diesel engine oil formulated to provide maximum protection under the most demanding conditions.

APPLICATION

Primarily designed to meet the demands of agricultural and off-highway vehicles requiring oil to ACEA E7, API CI-4 and Volvo VDS 3 performance levels. It also meets or exceeds the requirements for other Euro 3 and Euro 4 compliant heavy-duty diesel engines which are not fitted with emission control after-treatment systems, and do not require a low SAPS lubricant, and suitable for certain Euro 5 engines without particulate filters. Also suitable for use in heavy duty truck and bus applications where this specification of oil is required.

BENEFITS

- Capable of achieving maximum oil drain periods, both in and out of warranty.
- Excellent detergent/dispersant package promotes engine cleanliness and effective soot dispersancy.
- Improved wear protection and lubricant stability.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- ACEA E7, E5
- API CI-4, SL
- JASO DH-1
- Mercedes-Benz 228.3
- MAN 3275
- Volvo VDS 3
- Renault RVI RLD-2
- Mack E-OM Plus
- Cummins 20077/78
- MTU Type 2
- Caterpillar ECF-1a
- Deutz DQC III

TYPICAL PROPERTIES

Specific Gravity @ 15°C| 0.881 Kinematic Viscosity @ 40°C (cSt)| 94.1 cSt
Kinematic Viscosity @ 100°C (cSt)| 13.6 Viscosity Index| 146 Pour Point |-30°C
Flash point |>200°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.