AGRISTAR ULTRA UHPD 10W40

Last Updated: 17.08.2026
Product Code: AT0411

AGRISTAR ULTRA UHPD 10w40 is a full synthetic, low SAPS (Sulphated Ash, Phosphorus and Sulphur) diesel engine oil for use in heavy duty Euro 4, Euro 5 and many Euro 6 engines.

APPLICATION

Designed for modern off-highway plant and equipment operating under severe conditions. Primarily formulated for the lubrication of Euro 4, Euro 5 and Euro 6 diesel engines equipped with Diesel Particulate Filter (DPF) or catalytic after treatment system (such as SCR) and offers elevated levels of engine protection even when operating over extended oil drain periods. Also suitable for use in heavy duty truck and bus applications where this specification of oil is required.

BENEFITS

Formulated for use where ACEA E7, ACEA E8 and ACEA E11 applications are specified
• Elevated anti-wear and anti-corrosion properties
• Protects catalytic after treatments systems (SCR)
• Exceptional protection against bore polishing and cam wear
• Offers prolonged oil drain intervals thereby reducing maintenance costs
• Enhanced thermal stability for extended fluid life
• Formulated to greatly reduce carbon contamination within the engine crankcase

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;
• ACEA E7, E8, E11
• ACEA E6, E9 (still suitable for use where these older requirements are specified)
• API CK-4
• Mercedes-Benz 228.51
• Volvo VDS 4.5
• Renault RVI RLD-3
• MACK EO-S 4.5
• MAN M3477, M3271-1
• CAT ECF-3
• Cummins CES 20076, 20077
• Deutz DQC III-10 LA
• DAF extended drain requirement

TYPICAL PROPERTIES

Specific Gravity @ 15°C| 0.859 Kinematic Viscosity @ 40°C (cSt)| 83.1 cSt
Kinematic Viscosity @ 100°C (cSt)| 13.1 Viscosity Index| 159 Pour Point |-40°C
Flash point (closed) | 189°C
Sulphated Ash (% Wt)|<1.0%
TBN| 10.5

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our

product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963