AGRISTAR UHPD 15W40

Last Updated: 08.09.2026
Product Code: AT0412

AGRISTAR UHPD 15w40 is a semi synthetic heavy duty engine oil especially suitable for vehicles equipped with after-treatment systems which require a low SAPS (Sulphated Ash, Phosphorus & Sulphur) engine oil.

APPLICATION

Designed to meet the stringent requirements imposed on today's emission-controlled engines by the latest Euro 5 and 6 regulations. Recommended for vehicles which require Volvo VDS 4.5, Renault RLD-3, CAT ECF-3, Mercedes-Benz 228.31, Cummins CES 20086, ACEA E11 and API CK-4 specifications, as well as many other heavy-duty and off-highway diesel applications which require a modern, fuel-efficient lubricant of this type, including Case New Holland, Hitachi, Isuzu, JCB, John Deere, Kobelco, Komatsu and Liebherr.

BENEFITS

- Specifically formulated to meet heavy-duty diesel API CK-4, ACEA E11 and Euro 6 requirements.
- Suitable for use where the older ACEA E9 specification is listed.
- Excellent wear protection and lubricant stability, even under severe operating conditions.
- Outstanding soot handling and oxidation control.
- Suitable for engines with or without particulate filters, as well as EGR and SCR emissions reduction systems.
- High detergent and dispersion levels.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;
- API CK-4
- ACEA E11, E7
- ACEA E9 (still suitable for use where this older requirement is specified)
- JASO DH-2
- Volvo VDS 4.5
- Renault RVI RLD-3
- Mack EO-S 4.5
- Mercedes-Benz 228.31
- Cummins CES 20086
- MAN M3575
- MTU Type 2.1
- Caterpillar ECF-3
- Deutz DQC-III-10 LA

TYPICAL PROPERTIES

Specific Gravity @ 15°C | 0.864
Kinematic Viscosity @ 100°C (cSt) | 13.5 cSt
TBN | 10.5
Flash point | >220°C
Sulphated Ash, Wt (%): < 1.0

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963