AUTOTRANS DCT/DSG FLUID

Last Updated: 09.01.2025
Product Code: AD0069

AUTOTRANS DCT/DSG FLUID is a very high performance, fully synthetic formulation to meet the exacting requirements of the latest wet-clutch DCT (Dual Clutch Transmission) and DSG (Direct Shift Gearbox) units fitted in many modern vehicles.

APPLICATION

Designed primarily for the DSG transmissions found in many VW, AUDI, SKODA and SEAT vehicles. Also meets the exacting requirements for the DCT systems in many BMW, MERCEDES-BENZ, VOLVO and FORD models, as well as many transmissions of this type supplied by manufacturers such as ZF, Borg Warner and Getrag to meet the OEM specifications as listed below.

Note: Not suitable for dry-clutch DCT applications.

BENEFITS

- Superior high torque capability offers protection even with high performance operations.
- Formulated to provide maximum transmission efficiency and fuel economy even in hot conditions.
- Exceptional low temperature properties.
- Excellent protection against foaming and corrosion.
- Compatible with all types of transmission seal materials.
- Outstanding oxidation stability and anti-wear protection for longer fluid and component life.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- ATF BOT 450, BOT 341, FFL-2, FFL-3, FFL-4, TF DCT-F3
- BMW 7 Speed (Getrag) / DCTF-1, 83 22 0 440 214
- BMW DCTF-1+, DCTF-2, 6-speed DCT
- BMW MTF LT-5, 83 22 2 167 666
- BUGATTI Veyron
- CHRYSLER Powershift (6 Speed), 68044345 EA / GA,
- FERRARI 7 Speed (Getrag) / TF DCT-3
- FIAT 9.55550- HE2, 9.55550-MZ6
- FORD Powershift (6 Speed), M2C 936A
- MERCEDES-BENZ 236.21 (7G-DCT)
- MITSUBISHI Dia-Queen SSTF-1, MZ320065
- PEUGEOT/CITROEN PSA 9734.S2
- PORSCHE PDK 999.917.080.00, 999.917.080.01
- RENAULT EDC 6 speed (Getrag), EDC 7
- VOLVO Powershift 6 Speed (GFT) 1161838, 1161839
- VW/AUDI G 052 182 A2, G 052 182 A6, VW TL 521 82
- VW/AUDI G 052 536, G 055 536, G 052 512
- VW/AUDI G 052 529 A2/A6 (S-Tronic), G 055 529 (ZF)
- VW GOLF GTE DQ400E
- Not recommended for CVT transmission

TYPICAL PROPERTIES

Appearance	Amber
Specific Gravity @ 15°C	0.845

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963

Kinematic Viscosity @ 100°C (cSt)	7.7 (typical)
Flash Point COC °C	199
Pour Point °C	– 50

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963