AUTOTRANS SYNTH

Last Updated: 09.01.2025
Product Code: AD0065

AUTOTRANS SYNTH is a premium automatic transmission fluid blended from synthetic base fluids and highly refined mineral oil.

APPLICATION

For use in automatic transmissions, powershift transmissions, fluid couplings, transfer boxes, trans-axles and torque convertors etc. in accordance with the manufacturer's specifications. Backward compatible to all Dexron II applications.

BENEFITS

- Resistant to high temperatures associated with "stop start" operating conditions
- Excellent frictional characteristics
- Good seal compatibility
- Exceptional oxidation stability
- Superior low temperature properties
- Suitable for hydraulic systems with large temperature fluctuations

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- GM Dexron IIIH, IIIG
- FORD Mercon, M2C-138CJ, M2C-166H
- ALLISON C4, TES-389
- ATF 3403, M115, LA2334, LT71141,
- BMW LA2634, LT71141, 7045E, ETL-8072B
- CAT TO-2
- CHRYSLER/JEEP/DODGE ATF +2 and ATF +3
- HYUNDAI/KIA SPII
- JAGUAR ATF 3403 M115, JLM 20238, JLM 20292
- MAZDA ATF M-III, F-1
- MB 236.1, 236.5, 236.6, 236.7, 236.9, 236.10
- MAN 339 Z1, V1, Z2, V2
- PORSCHE 000 043 205 09
- PSA (PEUGEOT/CITROEN) AL4
- RENAULT DPO/AL4
- TOYOTA ATF D-III
- VOITH 55.6335, 55.6336
- VOLVO 97335, 97340, 97341 (AT101)
- VW G 052 162 A2
- ZF TE-ML 02F, 03D, 05L, 09, 21L
- ZF all 3 & 4 speed auto transmissions
- ZF 5HP 18FL/19FL/24/24A/30
- Not recommended for CVT or DCT transmissions

TYPICAL PROPERTIES

Appearance	Red
Specific Gravity @ 15°C	0.854
Kinematic Viscosity @ 100°C (cSt)	7.5 (typical)

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963

Flash Point (°C)	195
Pour Point °C	– 51

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.