AUTOTRANS TYPE G

Last Updated: 09.01.2025
Product Code: AD0066

AUTOTRANS TYPE G is a high quality automatic transmission fluid manufactured from a blend of solvent- refined base oils and a state-of-the-art additive package to provide the desired non-frictional modified properties required in this product.

APPLICATION

For use in automatic transmissions, gearboxes, hydraulic systems, power steering units, fluid drives and torque converters requiring a non-friction modified transmission fluid, such as many early Ford, Volvo, Jaguar, Mazda and Toyota vehicles, especially those fitted with early Borg Warner and Aisin Warner transmissions. Also meets the requirements of John Deere J21A specification.

Please check vehicle handbook for compatibility with manufacturer requirements.

BENEFITS

- Non-friction modified formulation as required by this specification of product
- Excellent wear and corrosion resistance
- Good seal compatibility
- Exceptional oxidation stability
- Formulated to resist foaming

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- FORD ESP M2C-33G
- FORD ESP M2C-33F
- John Deere J21A

TYPICAL PROPERTIES

Appearance	Red
Specific Gravity @ 15°C	0.865
Kinematic Viscosity @ 100°C (cSt)	7.4 (typical)
Flash Point (°C)	>200
Copper Corrosion	Nil

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963