AXLE-PRO GEAR OILS 80W-90

Last Updated: 09.01.2025
Product Code: AG0650

AXLE-PRO GEAR OILS 80W-90 is a premium quality, heavy-duty, hypoid axle and gear lubricants formulated to meet many of the latest OEM specifications and requirements, and incorporating the very latest additive technology combined with high quality solvent refined base stocks.

APPLICATION

Designed primarily for use in the latest designs of axles found in many late-model trucks and buses from a wide variety of manufacturers, as well as for all non-synchronized manual transmissions used in buses and heavy-duty trucks which require an API MT-1 specification lubricant.

BENEFITS

- Exceptional protection from wear over extended periods.
- Enhanced anti-corrosion and anti-oxidation characteristics for longer component life.
- Excellent load-carrying ability, even under arduous operating conditions.
- Formulated to impart improved performance and protection across a wide temperature range.

PERFORMANCE PROFILE

- API GL-5, API MT-1
- MIL-PRF 2105E
- SAE J-2360
- SCANIA STO 1:0
- MACK GO-J
- Arvin Meritor Axles
- MAN 342 Type M2
- MB 235.20 (80w90)
- ZF TE-ML 05A, 07A, 12E, 16B, 17B, 19B, 21A

TYPICAL PROPERTIES

Density @ 15.6°C	0.899
Viscosity @ 40°C	205.3 cSt
Viscosity @ 100°C	15.0 cSt

Viscosity Index – 105

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963