

AXLE-PRO S GEAR OIL 75W-140

Last Updated: 17.08.2026
Product Code: AG0662



AXLE-PRO S 75w140 is a premium quality, heavy-duty axle and transmission lubricant formulated to meet many of the latest OEM specifications and requirements, and incorporating the very latest additive technology combined with high quality synthetic base stocks.

APPLICATION

Designed primarily for use in the latest designs of commercial vehicle transmissions and axles found in many late-model trucks and buses from a wide variety of manufacturers, as well as for all non-synchronized manual transmissions used in buses and heavyduty trucks which require an API MT-1 specification lubricant. Also suitable for many off-highway and plant applications, as well as high performance and sports cars where a product of this type is specified.

BENEFITS

- Exceptional protection from wear over extended drain periods.
- Enhanced anti-corrosion and anti-oxidation characteristics for longer component life.
- Excellent load-carrying ability, even under arduous operating conditions.
- Formulated to impart improved performance and protection across a wide temperature range.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API GL-4, GL-5
- API MT-1
- MIL-PRF 2105E
- SAE J-2360
- SCANIA STO 1:0
- MACK GO-J
- Arvin Meritor Axles
- ZF TE-ML 05A, 05B, 07A, 08, 12B, 16F, 19C

TYPICAL PROPERTIES

Density @ 15.6°C | 0.8730
Viscosity @ 40°C (cSt) | 225.4
Viscosity @ 100°C (cSt) | 28.2
Viscosity Index | 162.3

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.