GEAR-PRO S 75W-85

Last Updated: 17.08.2026
Product Code: AG0661

GEAR-PRO S 75w85 is a high performance, fuel-efficient, full synthetic lubricant for use in highly stressed modern drive-line components. Formulated to meet the latest specifications and requirements of many of today's passenger car, truck and bus manufacturers, it incorporates the very latest additive technology combined with high quality synthetic base stocks.

APPLICATION

Designed primarily for use in the latest designs of drive-line components such as transmissions, axles, transfer cases and final drives, either with or without limited slip requirements. Suitable for many late model passenger cars, vans, trucks and buses from a wide variety of manufacturers, as well as for off-highway and plant applications which require this specification of lubricant.

BENEFITS

• Low viscosity formulation imparts improved performance across all temperatures.
• Designed to enhance fuel economy compared to SAE 80w and 90w gear oils.
• Enhanced friction modification chemistry enables use in limited slip differentials.
• Excellent protection from wear over extended periods.
• Enhanced anti-corrosion and anti-oxidation characteristics for longer component life.
• Synthetic formulation ensures improved performance throughout fluid life which is well in excess of conventional mineral oils.
• Outstanding load-carrying ability, even under the most arduous operating conditions.

PERFORMANCE PROFILE

Suitable for use where the following requirements are specified;
• API GL-5 and GL-5 LS
• SAE J-2360
• BMW Hypoid Axle Oil G1/8222295532
• BMW Hypoid Axle Oil G2/8222413511
• BMW Hypoid Axle Oil G5/8222471487
• BOT 448, BOT 799
• DAIMLER TRUCK DTFR 12B120
(previously MB 235.31)
• FCA/FIAT 9.55550-DA8, 9.55550-DA9
• FORD M2C 942-A
• HONDA Hypoid Gear Oil HGO-1
• LAND ROVER LR052059, LR129319
• LEXUS/TOYOTA LSD DIFFERENTIAL OIL LX
• MOPAR 68083381AA
• MERCEDES-BENZ MB 235.15, MB 235.33
• MERCEDES-BENZ MB 235.62, MB 235.74
• VW G 052 190, G 052 518
• VW G 055 190, G 060 190

TYPICAL PROPERTIES

Density @ 15.6°C| 0.862
Viscosity @ 100°C (cSt)| 11.7
Viscosity @ 40°C (cSt)| 64.4
Flash Point (CoC) °C| 215
Pour Point °C| -51

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963