

FLEETLUBE 10W-40 is a mixed fleet engine oil suitable for use in both petrol and diesel engines.

APPLICATION

Suitable for use in all types of vehicles including heavy-duty diesels, light commercials, vans and cars, as well as agricultural equipment and off-highway vehicles where this specification of oil is required by the engine manufacturer.

Please note - Not suitable for vehicles meeting EURO 4 or later emission standards, and which require a low SAPS lubricant.

BENEFITS

- High shear stability.
- Promotes easy starting in cold conditions.
- Suitable for both turbocharged and normally aspirated petrol and diesel engines.
- Enhanced anti-wear performance for reduced engine wear.
- Excellent sludge control for stop-go city motoring.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required;

- API CG-4/SJ
- ACEA E2
- Mercedes-Benz 228.1
- MAN 271

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.888
Kinematic Viscosity @ 100°C (cSt)	13.82
Kinematic Viscosity @ 40°C (cSt)	95.51
VI	147
Flash Point COC (°C)	220
Pour Point (°C)	-32
TBN mg KOH/g	9.18

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.