FLUSHING OIL – INDUSTRIAL

Last Updated: 09.01.2025
Product Code: FLUSH

FLUSHING OIL – INDUSTRIAL is formulated from specially selected solvent-refined mineral oils which impart excellent natural cleaning properties, and is suitable for most types of industrial applications.

APPLICATION

Recommended for the flushing of many industrial applications where a mineral-oil based system needs to be flushed prior to refilling with fresh oil.

BENEFITS

- Exceptional natural cleaning properties.
- Compatible for use in all mineral oil based systems.
- Excellent versatility for use in most types of industrial applications.

TYPICAL PROPERTIES

Kinematic Viscosity @ 40°C (cSt): – 10-13

Specific Gravity @ 15°C	0.880
Flash Point (Closed Cup) °C	>190

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963