HYPOID GEAR OILS SAE 85W-140 GL-5

Last Updated: 09.01.2025
Product Code: AG0351

HYPOID GEAR OILS SAE 85W-140 GL-5 is a heavy duty hypoid axle lubricant.

APPLICATION

A hypoid gear oil formulated for use in a wide variety of gearboxes and axles requiring high levels of extreme pressure (EP) performance to API GL-5 specification in various viscosities.

BENEFITS

- Specially selected additives combined with high quality solvent refined base stocks including enhanced EP performance.
- Excellent protection from wear
- Anti-rust characteristics
- Good oxidation stability
- Imparts exceptional load carrying ability

PERFORMANCE PROFILE

- Meets or exceeds API GL-5 / MIL-L-2105D

TYPICAL PROPERTIES

Density @ 15.6°C	0.899
Viscosity @ 40°C	420.0 cSt
Viscosity @ 100°C	28.0 Cst
Viscosity Index	92
Flash Point (PMCC)	210°C
Pour Point	– 15°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963