MIXER MOULD OIL

Last Updated: 09.01.2025
Product Code: CM0093

MIXER MOULD OIL is a high quality blend of solvent refined mineral oil and specialist release agent additives designed for use as a mould release agent and also for pre-treatment and cleaning of concrete/cement mixing equipment.

APPLICATION

Promotes excellent mould release, and is ideal for the pre-treatment and cleaning of all types of concrete/cement mixing equipment. Suitable for application by spray, roller or brush, and compatible with most mould materials.

Please check compatibility before application and use in accordance with equipment manufacturers recommendations.

BENEFITS

- Suitable for use on most surfaces including metals, sealed wood, fiberglass, plastics etc.
- Provides good surface finish together with excellent mould release properties.
- Exceptional performance characteristics prevent bonding and facilitate easier clean up when used in mixing equipment.
- Easy application by spray, roller or brush.

TYPICAL PROPERTIES

Appearance	Amber fluid
Viscosity @40°C	4.8 cSt
Specific gravity @15.6°C	0.8322
Flash Point (COC)	>62°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963