PENETRATING OIL HF

Last Updated: 09.01.2025
Product Code: IA0063

PENETRATING OIL HF is formulated to work quickly and effectively to free rusted or difficult to remove nuts, bolts, chains and locks, and to offer a higher flashpoint when working in elevated temperature environments.

APPLICATION

Use as received – apply by spray, brush or dipping in a well-ventilated area.

BENEFITS

- Excellent penetration qualities.
- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Offers excellent corrosion protection properties.
- Non-staining formulation.

TYPICAL PROPERTIES

Appearance	Pale Yellow fluid
Odour	Light paraffinic
Kinematic viscosity @ 40^{0}C	2 cSt
Specific gravity @15.6°C	0.809
Flash Point (COC)	85°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963