

# PENETRATING OIL HF

Last Updated: 09.01.2025  
Product Code: IA0063

**S|AIR** Lubricants

PENETRATING OIL HF is formulated to work quickly and effectively to free rusted or difficult to remove nuts, bolts, chains and locks, and to offer a higher flashpoint when working in elevated temperature environments.

## **APPLICATION**

Use as received – apply by spray, brush or dipping in a well-ventilated area.

## **BENEFITS**

- Excellent penetration qualities.
- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Offers excellent corrosion protection properties.
- Non-staining formulation.

## **TYPICAL PROPERTIES**

|                            |                   |
|----------------------------|-------------------|
| Appearance                 | Pale Yellow fluid |
| Odour                      | Light paraffinic  |
| Kinematic viscosity @ 40°C | 2 cSt             |
| Specific gravity @15.6°C   | 0.809             |
| Flash Point (COC)          | 85°C              |

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.