QUENCHING OIL Q22

Last Updated: 09.01.2025
Product Code: IQ0082

QUENCHING OIL Q22 is a highly refined, low viscosity, low sulphur content general purpose quenching oil.

APPLICATION

QUENCH OIL Q22 is a universal quench oil recommended when quenching direct from cyanide salt furnaces. Can be used for other hardening processes as well as a cyanide quenching.

Use as received. Ensures excellent quenching characteristics, providing good oxidation stability and low volatility.

BENEFITS

- Low viscosity.
- Low sulphur content.
- Good stability.
- Resists thickening up by oxidation.

TYPICAL PROPERTIES

Typical Kinematic Velocity @ 40°C (mm2 /s)	21.2
Typical Kinematic Viscocity @ 100°C (mm2 /s)	4.1

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963