# QUENCHING OIL Q32

Last Updated: 09.01.2025
Product Code: IQ0032

QUENCHING OIL Q32 is a highly refined, low viscosity, low sulphur content general purpose quenching oil

## APPLICATION

Use as received. Ensures excellent quenching characteristics whilst providing good oxidation stability, low volatility and low drag-out losses. Optimum operating bath temperatures 25 – 800C.

## BENEFITS

- Formulated with highly refined base oils.
- Low sulphur content.
- Reduced oxidation levels.

## TYPICAL PROPERTIES

| | |
|---|---|
| Kinematic Velocity @ 40°C (mm2) | 28.8-35.2 |
| Kinematic Velocity @ 100°C (mm2) | 5.3 |
| Specific Gravity @15.6°C | 0/875 |
| Flash Point (PMCC) °C | 178 min |
| Pour Point °C | -12 |

## HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

**SAR LUBRICANTS** (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963