RING OIL 100

Last Updated: 09.01.2025
Product Code: RING 100

RING OIL 100 is formulated for the lubrication of a wide variety of spinning and twisting rings including sintered rings.

APPLICATION

Use as received for the lubrication of ring spinning including solid and sintered rings.

BENEFITS

- Different viscosities available for different yarn counts.
- Excellent oxidation and wear resistance.
- Scourable properties ensure easy removal from fabric.
- Selected additives promote clear running.

TYPICAL PROPERTIES

Appearance	Pale Amber Oil
Specific Gravity @15.6°C	0.898
Viscocity@ 40°C	90-100 cSt
Pour Point	Below -5°C
Cloud Point	>70°C
Moisture	0.5%

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963