

ROCK DRILL OIL 320

Last Updated: 17.08.2026
Product Code: RD0320



ROCK DRILL OIL 320 is a high-quality, light viscosity oil specially designed for the lubrication of all types of airopowered rock drills, air hammers and other pneumatic equipment which requires this grade of product.

APPLICATION

Primarily recommended for pneumatic percussion-type rock drills, jackhammers and piledrivers, as well as other airopowered equipment such as airsaws, riveters and torque wrenches used in mining, quarrying, construction and excavation industries. The lighter grade ensures suitability for all-season operations.

BENEFITS

- Exceptional EP and anti-wear capabilities to provide protection even in the most demanding conditions.
- Formulated for maximum rust and corrosion resistance for extended component life.
- Low viscosity ensures rapid circulation to get to work faster.
- Excellent anti-foam properties ensures quick release of air from the oil.
- The addition of a tackiness additive ensures a constant oil film on cylinder walls and other drill parts even during severe operations.

TYPICAL PROPERTIES

Colour & Appearance| Brown liquid
Density kg/m³@ 20°C| 0.896
Kinematic Viscosity cSt @ 40°C| 320
Flash Point °C| >225
Pour Point °C| -39

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.