

RUNNING-IN OIL SAE 30

Last Updated: 09.01.2025
Product Code: AE0018



RUNNING-IN OIL SAE 30 is designed to be used for the short-term running-in of new or reconditioned diesel and petrol engines.

APPLICATION

Formulated to allow the correct bedding-in of pistons/piston rings within the cylinder bores in new and rebuilt or reconditioned engines.

Running-In Oil SAE 30 is designed to permit a controlled bedding-in process to occur.

Try to take the engine steadily up and down through the rev range, avoiding both excessive high revs/stress and excessive low revs/labouring for a maximum of 500 miles or 20 hours before being refilled with the correct specification of oil recommended by the engine manufacturer.

BENEFITS

- Can be used for both on-road and test bed running-in processes.
- Optimises long-term performance.
- Promotes longer-term fuel efficiency.
- Reduces excessive oil consumption as a result of cylinder bore glaze.

PERFORMANCE PROFILE

- SAE 30

TYPICAL PROPERTIES

Specific Gravity @ 15.6°C	0.876
Kinematic Viscosity @ 100°C (cSt)	11.5
VI	101
Flash Point COC (°C)	>220
Pour Point (°C)	-30

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.