# SARCUT 832

Last Updated: 03.09.2026
Product Code: MW0832

SARCUT 832 is an extreme-pressure, neat cutting oil formulated with a blend of high-quality, low aromatic mineral and synthetic components and a carefully balanced additive system.

## APPLICATION

Suitable for use in applications where high levels of extreme pressure additives are required, such as fine blanking, forming and piercing on high speed transfer presses, as well as heavy duty broaching operations and other metalworking operations where high levels of EP performance are required.

## BENEFITS

- Low odour promotes a high level of operator acceptability.
- Multi-metal compatibility – non-staining towards yellow metals, brass, copper etc.
- Formulated to protect and extend the life of tooling and enhance component finish.
- Low viscosity ensures good flushing of machine swarf and debris.

## TYPICAL PROPERTIES

| | |
|---|---|
| Appearance | Clear pale straw liquid |
| Odour | Low |
| Specific Gravity@ 15.60C | 1.015-1.020 |
| Viscosity @ 40°C | 25-28 cSt |
| Flashpoint | > 190°C |
| Sulphur | No |
| Chlorine | Yes |
| Ester | Yes |

## HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

**SAR LUBRICANTS** (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963