# SARCUT ASF 10

Last Updated: 09.01.2025
Product Code: MW0511

SARCUT ASF 10 is blended from solvent refined mineral oil using selected additives affording a high level of lubricity and EP performance. Chlorine free.

## APPLICATION

Suitable for machining a wide range of materials in various applications, including deep hole boring, broaching, heavy duty tapping, threading and gear cutting. Arduous operations are overcome using high performance EP package.

## BENEFITS

- Enhanced lubricity.
- Good workpiece visibility.
- Improved finish on machine parts.
- Low oil mist levels.
- Promotes extended tool life.

## TYPICAL PROPERTIES

| | |
|---|---|
| Appearance | Amber Fluid |
| Specific Gravity @ 15.6°C | 0.876 |
| Kinematic Viscosity @ 40°C | 9.0 – 11.0 cSt |
| Ester | Yes |
| Sulphur | Yes – Active |
| Chlorine | No |

## HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

**SAR LUBRICANTS** (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963