

SARCUT CF 10

Last Updated: 09.01.2025
Product Code: MW0182



SARCUT CF 10 is a low viscosity neat cutting oil with a high proportion of lubricity additives. Suitable for operations where no sulphur is required.

APPLICATION

Use as received for applications requiring a low viscosity oil. Chlorine EP additives and esters with excellent lubricity give outstanding performance on operations requiring no sulphur in the formulation, and can be used on ferrous and non ferrous (yellow) metals.

BENEFITS

- Low viscosity ensures good flushing of machine debris.
- Suitable for a variety of machining operations on yellow metals.
- Suitable for light to medium severity tapping, broaching and deep hole drilling operations.

TYPICAL PROPERTIES

| | |
|----------------------------|-----------------|
| Appearance | Amber Oil |
| Specific Gravity @ 15.6°C | 0.950 - 1.05 |
| Kinematic Viscosity @ 40°C | 9.00 - 11.4 cSt |
| Chlorine | Yes |
| Sulphur | No |
| Ester | Yes |

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.