

SARCUT HD2 HONING OIL

Last Updated: 09.01.2025
Product Code: MW0322



SARCUT HD2 HONING OIL is a blend of high quality solvent-refined mineral oil and a carefully balanced additive system and ideal for heavy duty and large diameter applications, such as industrial cylinders and tubes.

APPLICATION

Use as received as a heavy duty neat oil for honing operations or any other machining activities where a medium viscosity oil with excellent lubricity properties is required. Formulated to protect against staining of yellow metals.

BENEFITS

- Excellent cooling properties.
- Enhanced lubricity promotes superior metal wetting and improved surface finish.
- Anti-misting properties for increased operator acceptability.
- Low viscosity ensures exceptional flushing and retention of machined debris and swarf.
- Formulated with inactive sulphur to protect against yellow metal staining.

PERFORMANCE PROFILE

Extra heavy duty honing of ferrous and non ferrous materials, can also be used for grinding applications, drilling and general machining. ideal for heavy duty and large diameter applications, such as industrial cylinders and tubes.

TYPICAL PROPERTIES

| | |
|----------------------------|-------------------|
| Colour & Appearance | Amber fluid |
| Density @ 15.6°C | 0.890-0.900 kg/m3 |
| Kinematic Viscosity @ 40°C | 19-20 cSt |
| Chlorine | No |
| Sulphur | No |
| Ester | Yes |

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.