SARCUT L 8

Last Updated: 09.01.2025
Product Code: MW0008

SARCUT L 8 s a low viscosity high performance neat cutting oil, a chlorine free formulation with inactive sulphur, advanced lubricity additives and an anti-mist agent to improve operator and machine shop conditions.

APPLICATION

Use as received for applications requiring a low viscosity oil. Formulated with lubricity esters to give outstanding performance on operations requiring no sulphur or chlorine in the formulation, for ferrous and use on yellow metals.

Can be used for all forms of cutting, grinding and lapping operations and is suitable for use as a lubricating oil where a viscosity grade of ISO 10 is acceptable.

BENEFITS

- Low viscosity ensures good flushing of machine debris.
- Suitable for a variety of machining operations ferrous, yellow metals and sensitive aluminium alloys.
- Suitable for light to medium severity tapping, general machining and drilling operations.

TYPICAL PROPERTIES

Appearance	Pale Amber Oil
Specific Gravity @ 15.60C	0.836

Kinematic Viscosity @ 40C: 6.0 – 8.0 cSt

Chlorine: No

Sulphur: Yes

Ester: Yes

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963