SARDRAW 2204

Last Updated: 03.09.2026
Product Code: MW0930

SARDRAW 2204 is a custom blend of mineral oils and selected additives designed for use in heavy duty metal forming and drawing operations. (Product formerly known as SARFORM 2204)

APPLICATION

A metal working fluid for use in severe metal forming and drawing operations on steel and steel alloys. Typically used in blanking operations, sheet metal forming and similar applications.

BENEFITS

- Pale colour.
- Low odour and operator acceptability.
- Contains chlorinated EP additives.
- Corrosion inhibitor pack.
- Medium viscosity.
- High lubricity.
- Enhanced anti-misting properties, so user friendly.

TYPICAL PROPERTIES

Appearance	Amber liquid
Kinematic Viscosity @ 40°C	61.2 – 74.8 cSt
Specific Gravity @ 15.6°C	0.965

HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963