SARDRAW 250 M1

Last Updated: 03.09.2026
Product Code: MW0339

SARDRAW 250 M1 is a high-performance heavy duty drawing lubricant for the cold reduction of steel bar / bright bar. The combination of carefully selected additive technology and base oil structure ensures an extreme pressure performance for deformation of ferrous metals under arduous conditions.

APPLICATION

Designed for use on heavy duty to severe applications such cold forging, heavy duty stamping, cold reduction / drawing of ferrous materials.

BENEFITS

- Provides outstanding chlorine free performance.
- Good surface finish.
- Low odour.
- High flash point.
- Extended die life.
- Cost effective.
- Readily removed by solvent degreasing methods.

TYPICAL PROPERTIES

Kinematic Viscosity @ 40°C	250.0 cSt
Appearance	Pale Brown liquid
Flashpoint	> 200°C
Boiling Point °C	> 250°C

HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963