SARDRAW 32 ASF

Last Updated: 09.01.2025
Product Code: MW0932

SARDRAW 32 ASF is a high-performance general-purpose chlorine free drawing and stamping lubricant blended from solvent refined mineral oil using selected chlorine free additives affording a high level of lubricity and EP performance.

APPLICATION

Suitable for use on a wide range of ferrous materials, can be applied undiluted by dipping, roller, swab, or spray. This product is not recommended for use on non-ferrous materials due to the potential to discolour work piece materials. Post forming, the product can be removed by aqueous based cleaning solutions or cleaning solvent.

BENEFITS

- Enhanced lubricity.
- Low viscosity fluid.
- Excellent surface wetting, economical in use.
- Promotes extended tool life.

TYPICAL PROPERTIES

Appearance	Amber Fluid
Specific Gravity @ 15.6°C	0.885
Kinematic Viscosity @ 40°C	28.8 – 35.2 cSt

HEALTH & SAFETY, STORAGE AND DISPOSAL

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963