SARFOOD VHVI HYDRAULIC OIL 68

Last Updated: 09.01.2025
Product Code: SFV0068

SARFOOD VHVI HYDRAULIC OIL 68 is a food grade, non-toxic developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Also suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired.

APPLICATION

Sarfood VHVI Hydraulic Oils are suitable for hydraulic systems designed to operate in applications where ISO 68 oil viscosity grades are used. Follow manufacturer's instructions. It is important to purge the system of the previous oil prior to recharging with Sarfood VHVI Hydraulic Oils.

BENEFITS

- Low coefficient of friction provides excellent lubrication and reduces wear.
- Fully synthetic oil provides extremely wide temperature stability and ensures greatly extended servicing intervals.
- Low foaming reduces residue and scum build-up, which extends maintenance intervals.

PERFORMANCE PROFILE

- All ingredients are FDA listed
- Meets the requirements of NSF and InS H1 Guidelines
- Meets the USDA 1998 H1 Guidelines
- All grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives

TYPICAL PROPERTIES

Appearance	Clear Fluid
Base Fluid	Blend of Synthetic Oils
Temperature Range	– 15°C to + 180°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963