SARFORM 247

Last Updated: 09.01.2025
Product Code: CM0247

SARFORM 247 is a release agent specifically formulated to give easy release and high quality surface finishes to concrete in dry casting applications.

The product is formulated using highly refined mineral oils together with additives to give excellent release characteristics together with an enhanced surface finish.

APPLICATION

Use as received, suitable for use for in brick and concrete forming applications, may be by either brush, roller or spray, (use appropriate respiratory protection if spraying). Avoid excessive build-up of product, especially in tight angles.

- Dry casting of concrete forms
- Used on a wide variety of formwork
- Applied immediately prior to casting
- Fine spray achieved without clogging spraying equipment
- Good product mobility at low temperatures
- Can be used on most concretes

BENEFITS

- Provides quick release with reduced downtime and less damage to formwork.
- Reduces blowholes, surface blemishes and staining.
- Combines excellent lubricity and release.
- Contains excellent release additives.
- Light colour.
- Easy separation from the mould.

TYPICAL PROPERTIES

Appearance	Pale straw liquid
Specific Gravity @ 15°C	0.85
Viscosity @ 40°C	3.00 cSt
Flashpoint °C	> 110

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963