SARFORM 326

Last Updated: 09.01.2025
Product Code: CM0326

SARFORM 326 is a high quality low viscosity concrete mould release agent, formulated with a customised blend of selected hydrocarbon components fortified with chemical release agents, which react with concrete to form a barrier between the mould and casting.

APPLICATION

Use as received, application may be by either brush, roller or spray, (use appropriate respiratory protection if spraying).

Avoid excessive build-up of product, especially in tight angles. Apply on the form face to facilitate the easy removal of components from moulds without damaging the concrete surface.

BENEFITS

- Low viscosity formulation with mineral oil addition.
- Produces good surface finish.
- Excellent separation properties.
- Ease of application.
- Blemish free products.

TYPICAL PROPERTIES

Appearance	Thin, pale liquid
Specific Gravity @ 15°C	0.842
Viscosity @ 40°C	4.1 cSt
Flashpoint °C	70-80

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963