SARLUBE OIL 32

Last Updated: 09.01.2025
Product Code: IO0112

SARLUBE OIL 32 is a general purpose machine lubricant manufactured from a blend of solvent refined mineral oils.

APPLICATION

Use as supplied where non-additive lubricants are specified, recommended for lightly loaded industrial equipment with circulating systems, oil baths, automatic lubricators, spray, splash and mist lubricators. Suitable for oil lubricated bearings, machine tool headstocks, and enclosed gearboxes working in light to moderate conditions.

BENEFITS

- Excellent lubricity
- API GL1

TYPICAL PROPERTIES

Physical form	Liquid
Colour	Pale Amber
Odour	Oily
Boiling Point (Typical) °C	220
Viscosity @ 40°C (cSt)	28.8 – 35.2
Flashpoint °C (C.C)	197
Density @15.6 °C	0.867

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963