SARMAX HYDROL DETERGENT HYDRAULIC OILS – ISO 32

Last Updated: 09.01.2025
Product Code: HY0300

SARMAX HYDROL DETERGENT HYDRAULIC OILS – ISO 32is a premium quality hydraulic oils, manufactured from a blend of highly-refined mineral base oils and a multipurpose hydraulic oil additive package with enhanced detergent and dispersing properties.

APPLICATION

For use in both closed and total loss systems where a detergent hydraulic operating fluid is required.

BENEFITS

- Suitable for a wide range of industrial applications.
- Range of viscosities to meet most requirements.
- Reduced viscosity variation with temperature.
- Thermally stable in extreme conditions of temperature and load which supports resistance to degradation.
- Enhanced emulsifying properties to prevent water accumulation.
- Designed to finely disperse impurities and hold in suspension.

PERFORMANCE PROFILE

- DIN 51524 Part 2 (HLP-D)
- ASTM D6158 (HM)
- ISO 6743-4 (HM)

TYPICAL PROPERTIES

ISO Viscosity @ 40°C	32
ISO Viscosity @ 100°C	0.861
Pour Point °C	-25
Flash Point (COC) °C	206

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963