SARMAX ULTRA HYDRAULIC OILS – ISO 46

Last Updated: 09.01.2025
Product Code: HU0046

SARMAX ULTRA HYDRAULIC OILS – ISO 46 is a premium quality industrial hydraulic oil, manufactured from a blend of highly refined and high quality Group II base oils and a multipurpose hydraulic oil additive package.

APPLICATION

For use in both closed and total loss systems where a hydraulic operating fluid is required.

BENEFITS

- Suitable for a wide range of hydraulic and other industrial applications.
- Extensive range of viscosities to meet most requirements.
- Benefiting from a fourfold additive treatment which gives anti-wear, anti-oxidation, anti-corrosion and low foaming properties.
- Thermally stable in extreme conditions of temperature and load which supports resistance to degradation.

PERFORMANCE PROFILE

- DIN 51524 Part 2 (HM, HLP)
- ISO 11158 (HM)
- ASTM D6158 (HM)
- SAE MS1004 (HM)
- Parker-Denison HF-2, HF-1, HF-0 (ISO 32, 46, 68)
- Fives-Cincinnati P-68, P-69, P-70 (ISO 32, 68, 46)
- Eaton E-FDGN-TB002-E
- GB 11118.1-2011 (L-HL, L-HM)
- JCMAS P041 HK Hydraulic specification
- GM LS-2 (ISO 22, 32, 46, 68)
- SEB 181222
- AIST-US Steel 126/127 – R & O Hydraulic Fluids

TYPICAL PROPERTIES

ISO Viscosity @ 40°C, cSt	45.4
ISO Viscosity @ 100°C, cSt	6.9
Viscosity Index	108
Density @ 15°C, Kg/L	0.8671

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963