SARTEC 10

Last Updated: 09.01.2025
Product Code: IP0320

SARTEC 10 is a low viscosity rust preventative and water displacement fluid, which leaves a thin protective film.

APPLICATION

Use as received and apply by spray, brush or dipping.

BENEFITS

- Good dewatering properties.
- Provides short term protection of metal components when stored undercover.
- Easily removed with hydrocarbon solvent-based cleaners.
- Excellent penetration.
- Non staining.

PERFORMANCE PROFILE

Indoor Protection	3 Months
Outdoor Protection Covered	Not Recommended
Outdoor Protection Uncovered	Not Recommended

TYPICAL PROPERTIES

Appearance	Fluid Oil
Colour	Amber
Specific Gravity @ 15.6°C	0.811
Flash Point	64°C

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.

SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
Tel: +44 (0)1924 494371 | Email: enquiries@sarlubricants.co.uk
Registered in England: 05866783 VAT Registration No: 889171963