

# SARTEC 30 LS

Last Updated: 09.01.2025  
Product Code: IP0395



SARTEC 30 LS is a medium viscosity rust preventative dewatering fluid which leaves a thin protective film. Designed with a low-odour formulation for an enhanced working environment, it is a blend of corrosion inhibitors and waxes in a hydrocarbon base. Will give good indoor storage protection and some covered outdoor protection.

## **APPLICATION**

Use as received and apply by spray, brush or dipping in a well ventilated area. Leaves a waxy film on drying.

## **BENEFITS**

- Safe on ferrous and non-ferrous metals.
- Provides medium to long term protection of metal components when stored undercover.
- Easily removed with petroleum spirit or other hydrocarbon solvents.
- Good corrosion protection.
- Excellent penetration.
- Non staining.
- Ideal as a protection for agricultural machinery, metal stocks etc.

## **PERFORMANCE PROFILE**

Indoor Protection	6 Months
Outdoor Protection Covered	2-4 Months
Outdoor Protection Uncovered	Not Recommended

## **TYPICAL PROPERTIES**

Appearance	Fluid Oil
Specific Gravity @ 15.6°C	0.831
Colour	Amber
Flash Point	64°C
Kinematic Viscosity @ 40°C	8.5 cSt

## **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.