

SARTEC 606 is an oily corrosion preventive suitable for ferrous and non-ferrous materials giving outstanding protection for up to 12 months.

APPLICATION

Use as received and apply by brush, dip or spray, although its dewatering action is most effective if the articles to be protected can be immersed in a dip tank. The protective film can be removed by using aqueous or solvent based chemicals.

BENEFITS

- Excellent dewatering properties.
- Good corrosion protection.
- High resistance to emulsification.
- Lanolin free.
- Fast drying hydrocarbon solvent.
- Leaves a thin oily protective film, offering protection up to 12 months.
- Exceptional water separation promotes easy removal of settled water from the tank.

PERFORMANCE PROFILE

Indoor Protection	6 - 12 Months
Outdoor Protection Covered	Not Recommended
Outdoor Protection Uncovered	Not Recommended

TYPICAL PROPERTIES

Appearance	Light brown fluid
Flash Point	40°C
BS Type	2B
Specific Gravity	0.824
Humidity Cabinet Test	Pass <30 days

HEALTH & SAFETY

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health and disposal information which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.