# **SAR** Lubricants

SARTRAC STOU 15W-30 is a multipurpose lubricant suitable for use in agricultural tractor engines, transmissions, and hydraulic systems requiring these performance profiles.

## **APPLICATION**

Use as received in engines, transmissions, hydraulic systems, power take-off systems, power steering units, hydrostatic transmissions, and gear drive units when one multi-functional lubricant of this specification is recommended or required. A cost-effective grade, especially suitable for older equipment where more modern specifications are not a requirement.

### **BENEFITS**

- One oil for several applications, so reducing the number of grades needed in stock.
- Wide-ranging specification assures compliance with many manufacturer requirements.
- Reduces the risk of filling the wrong lubricant when several applications are due for changing.
- Excellent cold weather performance.
- Suitable for wet brake applications.

### **PERFORMANCE PROFILE**

Suitable for use where the following specifications are required:

- API CE / SF, API GL-4
- ACEA E2
- Ford M2C-159B
- Massey Ferguson M1135, M1139
- Allison C3
- John Deere J20A, J20B, J27
- CAT TO-2
- ZF TE-ML 06A

### **TYPICAL PROPERTIES**

Kinematic Viscosity @ 100°C	12.5 cSt
Specific Gravity @ 15.6°C	0.890

### **HEALTH & SAFETY**

Please refer to the Safety Data Sheet, freely available, for product handling and disposal advice. Please note that the SDS includes handling, storage, health, and disposal information, which should be passed on to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

NOTE: Read and understand all precautions on container labels before using this product.